




NATIONAL AERONAUTICS AND SPACE ADMINISTRATION




(NASA-CR-147608) AN INVESTIGATION TO
DETERMINE THE PRESSURE DISTRIBUTION ON THE
0.0137 SCALE SOLID ROCKET BOOSTER FOREBODY
(NSPC MODEL 467) AT ANGLES OF ATTACK AT OR
NEAR 90 DEG AND HIGH FREYNOLDS NUMBERS IN THE G3/18

N76-27343
HC 6.00

Unclas
45766

SPACE SHUTTLE

AEROTHERMODYNAMIC DATA REPORT



JOHNSON SPACE CENTER

HOUSTON, TEXAS

DATA Management services

SPACE DIVISION



CHRYSLER
CORPORATION

May, 1976

**DMS-DR-2207
NASA-CR-147,608
AN INVESTIGATION TO DETERMINE
THE PRESSURE DISTRIBUTION ON THE 0.0137 SCALE
SOLID ROCKET BOOSTER FOREBODY
(MSFC MODEL 467) AT ANGLES OF ATTACK AT
OR NEAR 90° AND HIGH REYNOLDS NUMBERS IN THE
MSFC HIGH REYNOLDS NUMBER WIND TUNNEL (SA29F)**

by

Paul E. Ramsey, NASA/MSFC

Prepared under NASA Contract Number NAS9-13247

by

**Data Management Services
Chrysler Corporation Space Division
New Orleans, La. 70189**

for

**Engineering Analysis Division
Johnson Space Center
National Aeronautics and Space Administration
Houston, Texas**

WIND TUNNEL TEST SPECIFICS:

Test Number: MSFC HRWT 033
NASA Series No.: SA29F
Model Number: 467
Test Dates: August 8 - September 18, 1974
June 25 - July 14, 1975

FACILITY COORDINATOR:

Mr. Dale Andrews
Marshall Space Flight Center
Mail Stop ED32
Huntsville, Alabama 35801

Phone: (205) 453-3174

PROJECT ENGINEER:


Mr. Paul E. Ramsey
Marshall Space Flight Center
Mail Stop ED32
Huntsville, Alabama 35801


Phone: (205) 453-3152

DATA MANAGEMENT SERVICES:

Prepared by: Liaison--V. W. Sparks
Operations--V. W. Sparks

Reviewed by: G. G. McDonald

Approved: 
J. L. Glynn, Manager
Data Operations

Concurrence: 
N. D. Kemp, Manager
Data Management Services

Chrysler Corporation Space Division assumes no responsibility for the data presented other than display characteristics.

AN INVESTIGATION TO DETERMINE THE PRESSURE
DISTRIBUTION ON THE 0.0137 SCALE SOLID ROCKET
BOOSTER FOREBODY (MSFC MODEL 467) AT ANGLES
OF ATTACK AT OR NEAR 90° AND HIGH REYNOLDS NUMBERS
IN THE MSFC HIGH REYNOLDS NUMBER WIND TUNNEL (SA29F)

by

Paul E. Ramsey, NASA/MSFC

ABSTRACT

An aerodynamic investigation was conducted in the MSFC High Reynolds Number Wind Tunnel to determine the pressure distribution over the fore-section of the current 146 inch diameter Shuttle SRB. The test model consisted of a 0.0137 scale version of the SRB nose cone and a forward portion of the cylindrical body which was approximately 2.7 calibers in length. The external configuration was defined by MSFC drawing number 10A00313 Revision A.

Data were obtained for Mach numbers of 0.4, 0.5, 0.6, 0.8, and 2.0; Reynolds numbers of from $2.3(10)^6$ to $20.1(10)^6$ based on body diameter; angle of attack of 72°, 90°, and 108°, circumferential body locations from 0° to 180°; and longitudinal station ratioed to body diameter (X/D) of from 0.340 to 2.160. Yaw was zero and no protuberances were fitted.

The pressure distributions are plotted as a function of longitudinal station ratioed to body diameter and circumferential location for

ABSTRACT (Concluded)

each angle of attack and Mach number. A Reynolds number variation study was made for Mach numbers of 0.4 and 0.6 at an angle of attack of 270° and roll angle of 180° .

TABLE OF CONTENTS

	Page
ABSTRACT	iii
INDEX OF MODEL FIGURES	2
INDEX OF DATA FIGURES	3
NOMENCLATURE	4
INTRODUCTION	6
TEST HARDWARE	8
INSTRUMENTATION	9
TEST FACILITY DESCRIPTION	10
DATA REDUCTION	11
REFERENCES	12
TABLES	
I. TEST CONDITIONS	13
II. DATA SET/RUN NUMBER COLLATION SUMMARY	15
III. MODEL DIMENSIONAL DATA	19
IV. ORIFICE NUMBERING SYSTEM	20
FIGURES	
MODEL	21
DATA	25
APPENDIX - TABULATED SOURCE DATA	

INDEX OF MODEL FIGURES

Figure	Title	Page
1	Body and Missile Axis Systems	21
2.	Details and Major Dimensions of SRB Forward Section and Sting	22
3.	Pressure Orifice Location and Identification System	23
4.	SRB Foresection Model Installed in the MSFC HRWT Transonic Test Section	24

INDEX OF DATA FIGURES

	SCHEDULE OF COEFFICIENTS PLOTTED	CONDITIONS VARYING	PAGES
PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY	(A)	THETA MACH ALPHA	1-46
PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY	(B)	X/D MACH ALPHA	47-78
EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS	(B)	RN X/D ALPHA MACH	79-90

PLOTTED COEFFICIENTS SCHEDULE:

- (A) CP versus X/D
- (B) CP versus THETA

NOMENCLATURE

General

<u>SYMBOL</u>	<u>PLOT SYMBOL</u>	<u>DEFINITION</u>	<u>UNITS</u>
C_p	CP	pressure coefficient; $(p_1 - p_\infty)/q_\infty$	
D		reference diameter (body diameter)	
l_B	LBODY	length of the ET	in.
M		Mach number	
P_1		local pressure	psi
P_t		total pressure	psi
P_∞		freestream pressure	psi
q_∞	Q(PSI)	freestream dynamic pressure unit	psi
R_N	RN	Reynolds number based on model diameter	
R_N/L	RN/L	Reynolds number per unit length	
SRB		Solid Rocket Booster	
S_{Ref}	SREF	base area or reference area, ft^2	
T_t		freestream total temperature ($^{\circ}F$)	deg.
X		distance from nose of SRB along X axis	in.
X_T, Y_T, Z_T		SRB stations	in.
X/D	X/D	longitudinal location of pressure measurement, expressed as a fraction of the SRB length, measured from the SRB nose	
P_0		plenum chamber pressure	psia

NOMENCLATURE (Concluded)

<u>SYMBOL</u>	<u>PLOT SYMBOL</u>	<u>DEFINITION</u>	<u>UNITS</u>
<u>GREEK SYMBOLS</u>			
α	ALPHA	angle of attack	deg.
ϕ	PHI	angle of roll	deg.
θ	THETA	circumferential location	deg.
<u>SUBSCRIPTS</u>			
ref		reference conditions	
∞		freestream conditions	
l		local	
t		total conditions	

INTRODUCTION

During the descent of the SRB, an atmospheric pressure switch or baroswitch will be used to initiate the Shuttle SRB parachute deployment system. This device will be located in a forward compartment which will be vented to the exterior environment. The internal pressure of this compartment is a function of the external conditions such as SRB velocity, attitude, and altitude which are predicted from aerodynamic force inputs into a dynamics analysis program. Based on the internal pressure, which corresponds to the desired parachute deployment altitude for a given entry trajectory, the baroswitch can be preset for recovery system initiation at the proper time. Initiation must occur within narrow altitude limits to assure the occurrence of the dynamic pressure needed for proper functioning of the parachute system. To obtain an accurate prediction of the forward compartment pressure needed to set the baroswitch, the external pressure distribution must be known for the full scale flight conditions.

Since the SRB will enter at an angle of attack near 90° where the flow around the body can be very sensitive to Reynolds number, a test Reynolds number as near to full scale as possible is necessary if adequate data are to be obtained.

Based on these observations, a test was conducted in the MSFC High Reynolds Number Wind Tunnel to determine the SRB forebody pressure distribution at 72° to 108° angle of attack. Pressures were measured over the nose cone and approximately one caliber of the cylindrical body. The

INTRODUCTION (Concluded)

Mach range consisted of 0.4, 0.5, 0.6, 0.8, and 2.0 at Reynolds numbers based on the SRB diameter. No protuberances were fitted for this investigation.

TEST HARDWARE

The model configuration consisted of a spherically blunted cone/cylinder which simulated the forward portion of the current 146-inch-diameter SRB. The model was mounted at the aft end with a 90° "dog leg" sting which was then supported in an available tunnel sting. Major dimensions of the model and sting are presented in Figure 2.

Because only 18 pressure tubes of 0.125-inch O.D. could be accommodated in the model, 4 interchangeable nose sections were provided, each containing 18 pressure orifices. The pressure tubing passed out of the nose through an O-ring sealed quick-disconnect system which allowed easy interchangeability of the nose sections. From this disconnect the tubing passed through cavities in the sting to the tunnel exterior.

No protuberances were included on the test models. The model diameter was 2 inches, which resulted in a scale of 0.0137. The MSFC model number is 467 and was fabricated using drawings 80M42699, 80M42700, 80M42714 - 80M42717, and 80M51377.

INSTRUMENTATION

The orifice location and arrangement are shown in Figure 3. The pressure lines were tubed to 18 Statham 1000 psia pressure transducers, which were monitored real time during each run. Combining data from each nose resulted in a total set of data for 72 orifice locations distributed over the test SRB configuration. In effect, four blows or runs were required to obtain a complete set of data for each test condition; i.e., Mach number, α , P_0 , and Reynolds number.

Two check orifices at thetas of $202\frac{1}{2}^\circ$ and $337\frac{1}{2}^\circ$ at longitudinal station 7 were included on nose 4 to give an indication of model misalignment or flow asymmetries. Because of the limited interior volume available near the front of the model, pressure taps were located on both sides of the nose for longitudinal station 1 on nose 4.

TEST FACILITY DESCRIPTION

The MSFC High Reynolds Number Wind Tunnel (HRWT) is a Ludwig tube tunnel capable of producing a Reynolds number range of 7×10^6 to 200×10^6 per foot over a Mach number range of 0.25 to 3.50. The test section is 32 inches in diameter by 64 inches in length.

The supply tube has a 52-inch inside diameter and is 386 feet long. It is terminated on one end with a hemispherical head and on the other end with a stilling chamber. The stilling chamber is 20 feet long and has a maximum diameter of 78 inches. The entrance cone has an 8-degree included angle.

The facility uses six interchangeable, axisymmetric, contoured nozzles. The diameters at the entrance and exit of each nozzle are 52 and 32 inches, respectively. The "sonic" nozzle is used to produce all subsonic and transonic speeds. The other five nozzles are designed for discrete Mach numbers 1.4, 1.7, 2.0, 2.75, and 3.5. Further details and performance characteristics of the HRWT are presented in Reference 1.

DATA REDUCTION

The data were reduced to pressure coefficients as follows.

$$C_p = \frac{P_1 - P_\infty}{q_\infty}$$

and tabulated in the format shown in Table IV. The data were also formatted for inclusion in the CCSD data management system. Tunnel test condition parameters such as run number, Mach number, α , q_∞ , T , RN , and P_0 are included in the tabulated data of the Appendix.

REFERENCES

1. Gwin, H. S., "The George C. Marshall Space Flight Center High Reynolds Number Wind Tunnel Technical Handbook," NASA TM X-64831, December 1973.

TABLE I.

TEST: MSFC HRWT 033		DATE: 10/17/75		
TEST CONDITIONS				
MACH NUMBER	REYNOLDS NUMBER (per unit length)	DYNAMIC PRESSURE (pounds/sq. inch)	STAGNATION TEMPERATURE (degrees Fahrenheit)	STAGNATION PRESSURE (pounds/sq. inch)
0.4	2.3×10^6	7.3	37	67.8
	4.0	13.4	51	128.1
	6.0	19.9	46	191.4
	7.5	25.4	49	238.8
	8.4	28.2	51	263.1
	8.9	30.2	49	286.8
	10.2	32.7	38	315.9
	13.3	44.6	48	424.2
	18.1	61.2	48	589.8
Y	18.8	61.3	44	590.1
0.5	18.1	75.2	49	506.7
0.6	2.8	13.0	48	64.3
T	4.0	18.7	41	92.2
	6.0	27.3	46	136.6
	7.5	34.4	51	175.4
Y	8.9	40.3	47	204.2

BALANCE UTILIZED: **NONE - STATHAM PRESSURE TRANSDUCERS**

	CAPACITY:	ACCURACY:	COEFFICIENT TOLERANCE:
NF	<u>1000 PSI</u>	<u>± 5 PSI</u>	<u>$\pm .06 @ q = 83 \text{ PSI}$</u>
SF	_____	_____	_____
AF	_____	_____	_____
PM	_____	_____	_____
RM	_____	_____	_____
YM	_____	_____	_____

COMMENTS:

TABLE I. (Concluded)

[illegible]**BALANCE UTILIZED:**

CAPACITY:

ACCURACY:

**COEFFICIENT
TOLERANCE:**

NF

SF

AF

PM

RM

YM

COMMENTS:

TEST: MSFC HRWT 035	DATE: 10/17/75
---------------------	----------------

TABLE II.

DATA SET/RUN NUMBER COLLATION SUMMARY

TEST: MSFC HRWT 035										DATA SET/RUN NUMBER COLLATION SUMMARY										DATE: 10/17/75									
DATA SET IDENTIFIER		CONFIGURATION		SCHD.		PARAMETERS/VALUES		NO. OF RUNS		MACH NUMBERS (OR ALTERNATE INDEPENDENT VARIABLE)										TEST RUN NUMBERS									
Q		P		S		φ		R _N		0.4		0.5		0.6		0.8		2.0											
R1E101		SRB NOSE		92		0		18.0		1				9		14													
				90						2				11		16													
				108						3				13		18													
				72								4																	
				80								5		10		15													
				90								6																	
				100								7		12		17													
				108								8																	
R1E103				72				9.0										19											
				80														20											
				90														21											
				100														22											
				108														23											
R1E104				72				8.4		37/1																			

TABLE II. (Continued)

DATE: 10/17/95										TEST RUN NUMBERS																		
DATA SET / RUN NUMBER COLLATION SUMMARY																												
DATA SET IDENTIFIER	CONFIGURATION	SCHD. PARAMETER		REYNOLDS NUMBER (OR ALTERNATE INDEPENDENT VARIABLE)																								
		α	β	ϕ	M	2.3	2.8	4.0	6.0	7.5	8.9	9.7	10.2	12.8	13.3	16.1	18.8	20.1										
R1E105	SRB NOSE	270	0	180	0.4			44/0	45/0	43/0	46/0				47/0		42/0											
R1E105	SRB NOSE	90	0	180	0.4	38/0							39/0															
R1E106	SRB NOSE	270	0	180	0.6		41/2	48/0	49/0	52/0	50/0	53/0		40/1	51/1	56/0	54/1											

TABLE II (Continued)
DATAMAN RUN NUMBER CORRELATION WITH TUNNEL RUN NUMBER

New Run Number	Tunnel Number	α	M
1	24/0, 19/0, 13/0, 18/0	72	0.4
2	1/0, 6/1, 12/1, 7/0	90	↓
3	25/0, 30/1, 36/0, 31/1	108	↓
4	57/0, 83/0	72	0.5
5	59/1, 79/0	80	↓
6	63/1, 77/2	90	↓
7	65/1, 73/0	100	↓
8	69/0, 71/3	108	↓
9	23/2, 20/0, 14/0, 17/0	72	0.6
10	60/1, 80/0	80	↓
11	2/0, 5/0, 11/1, 8/0	90	↓
12	66/1, 74/0	100	↓
13	26/0, 29/1, 35/0, 32/0	108	↓
14	22/2, 21/0, 15/0, 16/0	72	0.8
15	61/3, 81/0	80	↓
16	3/0, 4/0, 10/3, 9/0	90	↓
17	67/2, 75/0	100	↓
18	27/0, 28/0, 34/0, 33/0	108	↓
19	58/0, 84/0	72	2.0
20	62/0, 82/0	80	2.0

TABLE II. (Concluded)

New Run Number	Tunnel Number	α	M
21	64/2, 78/0	90	2.0
22	68/0, 76/1	100	2.0
23	70/0, 72/0	108	2.0

TABLE III.
MODEL DIMENSIONAL DATA

MODEL COMPONENT: BODY - SRB FORWARD SECTION

GENERAL DESCRIPTION: SPHERICALLY BLUNTED 18° HALF ANGLE NOSE CONE AND FORWARD PORTION OF CYLINDRICAL SECTION APPROXIMATELY 2.7 CALIBERS IN LENGTH.

SCALE = 0.0137

DRAWING NUMBER: MSFC DWG. 10A00313 REV. A

DIMENSIONS:	THEORETICAL		ACTUAL MEASURED
	FULL-SCALE	MODEL SCALE	MODEL SCALE
Length	<u>583.9 in.</u>	<u>8 in.</u>	<u> </u>
Max. Width	<u>146 in.</u>	<u>2 in.</u>	<u> </u>
Max. Depth	<u>146 in.</u>	<u>2 in.</u>	<u> </u>
Fineness Ratio	<u> </u>	<u> </u>	<u> </u>
Area			
Max. Cross-Sectional	<u>16,741.5 in.²</u>	<u>3.142 in.²</u>	<u> </u>
Planform	<u> </u>	<u> </u>	<u> </u>
Wetted	<u> </u>	<u> </u>	<u> </u>
Base	<u>16,497.6 in.²</u>	<u>3.096 in.²</u>	<u> </u>

Table IV. PRESSURE ORIFICE LONGITUDINAL/CIRCUMFERENTIAL LOCATIONS

NOSE NO. LONGITUDINAL STA. NO. X/D LONGITUDINAL LOCATION X (in.) CIRCUMFERENTIAL STA. NO. CIRCUMFERENTIAL LOCATION θ (deg.)	4		3			1			2	
	1	2	3	4	5	6	7	8		
	0.340	0.675	1.007	1.285	1.377	1.550	1.810	2.160		
0	A	8	17	26	35	44	53	62		
22 1/2	B	9	18	27	36	45	54	63		
45	C	10	19	28	37	46	55	64		
67 1/2	D	11	20	29	38	47	56	65		
90	E	12	21	30	39	48	57	66		
112 1/2	F	13	22	31	40	49	58	67		
135	G	14	23	32	41	50	59	68		
157 1/2	H	15	24	33	42	51	60	69		
180	I	16	25	34	43	52	61	70		
202 1/2	B'	---	---	---	---	---	71*	---		
337 1/2	H'	---	---	---	---	---	72*	---		

*Note that 71 and 72 are check orifices located on nose 4 and at longitudinal Station 7 position.




Figure 1. - Body and Missile Axis Systems




Figure 2. Details and Major Dimensions of SRB Forward Section and Sting




Figure 3. Pressure Orifice Location and Identification System





Figure 4. SRB Foresection Model Installed in the
MSFC HRWT Transonic Test Section

DATA FIGURES

MSFC HRWT 033 (S129F) SRB FORWARD NOSE SECTION (A1E101)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
	.000	72.100	.410	RN	.000 PHI
○	22.500				18.100
□	45.000				
◇	67.500				
△	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (A1E101)


SYMBOL	THETA	IA	MACH	BETA	PARAMETRIC VALUES
○	112.500	74.100	.410	RN	.000 PHI
□	135.000				18.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (A1E102)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
	.000	72.000	.500	RN	.000 PHI
○	22.500				18.100
□	45.000				
◇	67.500				
△	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (A1E102)


SYMBOL	PARAMETRIC VALUES	
	THETA	ALPHA
○	112.500	72.000
□	135.000	72.000
◇	157.500	72.000
△	180.000	72.000
	BETA	PHI
	RN	16.100
		.000



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E101)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
	.000	72.100	.600	RN	.000 PH1
○	22.500				18.100
□	45.000				
◇	67.500				
△	80.000				



Pressure Coefficient Along the Body at Various Positions Around the Body

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E101)

SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	72.100	.600	RN	.000 PHI
□	135.000				18.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E101)

SYMBOL
 □ ◇ △

THETA .000
 22.500
 45.000
 67.500
 90.000


ALPHA 72.100

MACH .760

BETA 18.100

RN .000


PARAMETRIC VALUES
 .000 PHI
 .000



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E101)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	72.100	.760	RN	.000 PHI
□	135.000				19.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC LPTWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E103)


SYMBOL	THETA		ALPHA		MACH		BETA		PARAMETRIC VALUES	
	.000	72.000	.000	9.000	.000	PHI	.000	9.000	.000	
□	22.500									
◇	45.000									
△	67.500									
▽	90.000									



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E103)

SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	72.000	2.000	RN	.000
□	135.000				9.000
◇	157.500				
△	180.000				




PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (CA29F) SR., FORWARD NOSE SECTION (B1E102)

SYMBOL	PARAMETRIC VALUES	
	BETA RN	PHI °
○	18.100	0.000
□	18.100	0.000
◇	18.100	0.000
△	18.100	0.000
▽	18.100	0.000


THETA °	ALPHA °	MACH
0.000	80.000	0.510
22.500		
45.000		
67.500		
90.000		



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E1U2)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	80.000	.510	RN	.000 PHI
□	135.000				16.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (129F) SRB FORWARD NOSE SECTION (BIE102)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
	.000	80.000	.600	RN	.000 PHI
□	22.500				18.100
◇	45.000				
△	67.500				
▽	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E102)

SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
□	112.500	80.000	.600	RN	.000 PHI
◇	135.000				18.100
△	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 0J3 (S429F) SRB FORWARD NOSE SECTION (B1E102)

SYMBOL
□ □ ◇ △


THETA
.000
22.500
45.000
67.500
90.000

ALPHA
80.000

MACH
.790

BETA
RN


PARAMETRIC VALUES
.000 PHI
18.100 .000



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E102)

SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	60.000	.750	RN	.000 PHI
□	135.000				18.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (C1E103)

PARAMETRIC VALUES
 .000 .000 .000
 PHI
 8.000


BETA
 RN

MACH
 2.000

ALPHA
 80.000

THETA
 .000
 22.500
 45.000
 67.500
 90.000


SYMBOL
 □ □ ◇ △ △



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (C1E103)


SYMBOL	PARAMETRIC VALUES	
	THETA	ALPHA
○	112.500	80.000
□	135.000	2.000
◇	157.500	
△	180.000	
	BETA	RN
	.000	9.000
	.000	.000



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HR#T 033 (SA29F) SRB FORWARD NOSE SECTION (C1E101)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
	.000	90.000	.400	RN	.000 PHI
□	22.500				
◇	45.000				
△	67.500				
▽	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (C1E101)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
□	112.500	90.000	.400	RN	.000 PHI
◇	135.000				18.100
△	157.500				
	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (C1E102)


SYMBOL	THETA	ALPHA	CACH	BETA	PARAMETRIC VALUES
○	.000	90.000	.490	RN	.000 PHI
□	22.500				18.100
◇	45.000				
△	67.500				
▽	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (C1E102)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	90.000	.490	RN	.000 PMJ
□	135.000				18.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E101)


SYMBOL	THETA		ALPHA		MACH		BETA		PARAMETRIC VALUES	
	.000	.000	90.000	90.000	.600	.600	RN	.000	.000	.000
□	22.500									
◇	45.000									
△	67.500									
▽	90.000									



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (DIE101)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	90.000	.600	RN	.000 PHI
□	135.000				18.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SR6 FORWARD NOSE SECTION (D1E101)


SYMBOL	PARAMETRIC VALUES	
	THETA	ALPHA
○	.000	90.000
□	22.500	.780
◇	45.000	
△	67.500	
▽	90.000	
	BETA	RN
	.000	18.100



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (DIE101)


SYMBOL	THETA	ALPHA	M/CH	BETA	PARAMETRIC VALUES
□	112.500	90 °00	.780	PHI	.000
◇	135.000			PHI	18.100
△	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HWWT 033 (SΛ29F) SRB FORWARD NOSE SECTION (D1E103)


SYMBOL	THETA	ALPHA	MACH	BETA	PHI
□	.000	90.000	2.000	.000	.000
◇	22.500			9.000	
△	45.000				
▽	67.500				
▲	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E103)

SYMBOL	PARAMETRIC VALUES	
	BETA RN	PHI .000
△	112.500	90.000
□	135.000	9.000
◇	157.500	
▽	180.000	



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E102)


PARAMETRIC VALUES
 .000 PHI
 18.100

BETA
 RN

ALPHA
 100.000
 .500

THETA
 .000
 22.500
 45.000
 67.500
 90.000


SYMBOL
 □ ◇ △ ▽



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E102)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	100.000	.500	RN	.000 PH: .000
□	135.000				
△	157.500				
◇	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRW J33 (SA29F) SRB FORWARD NOSE SECTION (OIE102)


SYMBOL	THETA .000	ALPHA 100.000	MACH .600	BETA RN	PARAMETRIC VALUES .000 PHI 18.100	.000
□	22.500					
◇	45.000					
△	67.500					
▽	90.000					



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E102)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
□	112.500	100.000	.600	RN	.000 PHI
◇	135.000				18.100
△	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (S.29F) SRB FORWARD NOSE SECTION (D1E102)


SYMBOL	THETA	ALPHA	MACH	BETA	PHI
□	.000	100.000	.790	.000	.000
◇	22.500			18.100	
△	45.000				
▽	67.500				
◊	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E102)

SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES	
○	112.500	100.000	.790	RN	.000	.000
□	135.000				18.100	
◇	157.500					
△	180.000					




PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (E1E103)

SYMBOL
 □ ◇ ◊ ◊

THETA .000 ALPHA 100.000 MACH 2.000
 22.500
 45.000
 67.500
 90.000


PARAMETRIC VALUES
 .000 PHI .000
 9.000 RN



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (E1E103)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
□	112.500	100.000	2.000	RN	.000
◇	135.000				9.000
△	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC H₂ VI 033 (S4.29F) SRB FORWARD NOSE SECTION (E1E101)


SYMBOL	THETA	ALPHA	MACH	BETA	PHI
○	.000	107.900	.410	18.100	.000
□	22.500				
◇	45.000				
△	67.500				
▽	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 003 (SA29F) SRB FORWARD NOSE SECTION (E1E101)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	107.900	.410	RM	.000 PHI
□	135.000				18.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT U33 (SA29F) SRB FORWARD NOSE SECTION (E1E1C2)


SYMBOL	THETA	ALPHA	MACH	BETA	PHI
□	.000	108.000	.500	RN	.000
◇	22.500				
△	45.000				
▽	67.500				
▲	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (E1E102)


SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	108.000	.500	RN	.000 PHI
□	135.000				18.100
◇	157.500				
△	180.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HWWT 033 (5A29F) SRB FORWARD NOSE SECTION (F1E101)


SYMBOL	THETA	ALP	MACH	BETA	PARAMETRIC VALUES
	.000	107.900	.610	RN	.000 PHI
□	22.500				19.100
◇	45.000				
△	67.500				
▽	90.000				



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (F1E101)

SYMBOL	THETA	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	112.500	107.900	.610	RN	.000 PHI
□	135.000				18.100
◇	157.500				
△	180.000				




PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 003 (SA29F) SRB FORWARD NOSE SECTION (F1E101)

SYMBOL
 O □ ◇ 4 4

THETA .000 ALPHA 107.900 MACH .760
 22.500
 45.000
 67.500
 90.000

PARAMETRIC VALUES
 .000 PHI .000
 18.100 RN



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (F1E101)

SYMBOL
 ○ □ ◇ △


THETA
 112.500
 135.000
 157.500
 180.000

ALPHA 107.900

MACH .760

BETA
 RN

PARAMETRIC VALUES
 .000
 .000
 PH1
 18.100



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRV J33 (29F) SRB FORWARD NOSE SECTION (F1E103)

SYMBOL
 □ ◇ △

THETA
 .000
 22.500
 45.000
 67.500
 90.000


ALPHA
 108.000

MACH
 2.000

BETA
 RN

PARAMETRIC VALUES
 .000 PHI
 9.000


.000



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (F1E103)


SYMBOL	THETA		ALPHA		MACH		BETA	PARAMETRIC VALUES	
	112,500	135,000	108,000	108,000	2,000	2,000		.000	.000
○							RN	9,000	
□									
◇									
△									



PRESSURE COEFFICIENT ALONG THE BODY AT VARIOUS POSITIONS AROUND THE BODY

MSFC HRWT 033 (S029F) SRB FORWARD NOSE SECTION (A1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
○	.340	72.100	.410		
□	.675				
◇	1.007				
△	1.265				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (A1E101)

SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	1.377	72.100	.410	RN	.000 PHI
□	1.550				18.100
◇	1.810				
△	2.160				




PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HPWT 033 (SA29F) SRB FORWARD NOSE SECTION (A1E102)

SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA	PHI
				RN	

.340 72.000 .500
 .675
 1.007
 1.285


.000
 18.100



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E101)


SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	.340	72.100	.600	RN	.000 PHI 18.100
□	.675				
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRW 033 (CA29F) SRB FORWARD NOSE SECTION (B1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
○	1.377	72.100	.600	18.100	.000
□	1.550				
◇	1.810				
△	2.160				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E101)

SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
○	.340	72.100	.760	18.100	.000
□	.675				
◇	1.007				
△	1.285				




PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HW 1 U33 (SA29F) SRB FORWARD NOSE SECTION (B1E101)

SYMBOL
 ○ □ ◇ △

X/D ALPHA MACH
 1.377 72.100 .760
 1.530
 1.810
 2.160


PARAMETRIC VALUES
 .100 PHI .000
 18.100 BETA RN



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E103)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI 9.000
○	.340	72.000	2.000		
□	.675				
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRW1 033 (SA29F) SRB FORWARD NOSE SECTION (B1E102)


SYMBOL	X/D	ALPHA		MACH		BETA RN	PARAMETRIC VALUES	
		.340	.675	.80.000	.510		.000	.000
□							18.100	
◇								
△								



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA295) FORWARD NOSE SECTION (BIE102)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
○	.340	80.000	.600	18.100	.000
□	.675				
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E102)


SYMBOL	X/O	ALPHA	FACH	PARAMETRIC VALUES	
				BETA RN	PHI .000 18.100 .000
□	.340	80.000	.790		
◇	.675				
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F). SRB FORWARD NOSE SECTION (C1E103)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
□	.340	80.000	2.000	9.000	.000
◇	.675				
△	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HWRT 03 (5A29F) SRB FORWARD NOSE SECTION (C1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI DEG
○	.340	90.000	400	.000	.000
□	.675			18.100	
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (C1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
□	1.377	90.000	.400	18.100	.000
◇	1.550				
△	1.810				
▽	2.160				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT J33 (SA29F) SRB FORWARD NOSE SECTION (C1E102)


SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALU--S
		90.000	.490	RN	.000 PHI
	.340				18.100
	.675				.000
	1.007				
	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (01E101)


SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALUES
	.340	90.000	.600	RN	.000
□	.675				18.100
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRW: 033 (S-29F) SRB FORWARD NOSE SECTION (D1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	.000 PHI 18.100 .000
○	1.377	90.000	.600		
□	1.550				
◇	1.810				
△	2.160				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA	.000 PHI
				RN	18.100
					.000
□	.340	90.000	.780		
◇	.675				
△	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (S429F) SRB FORWARD NOSE SECTION (D1E101)


SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALUES		
	1.377	90.000	.780		.000	PHI	.000
	1.550				18.100		
	1.810						
	2.160						



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC H. J33 (SA29F) SRB FORWARD NOSE SECTION (D1E103)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI RN
○	.340	90.000	2.000	.000	.000
□	.675			9.000	
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT J33 (SA29F) SP3 FORWARD NOSE SECTION (D1E102)

SYMBOL	X,0	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
○	.340	100.000	.500	18.100	.000
□	.675				
◇	1.007				
△	1.285				




PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E102)

SYMBOL
○ □ △

X/D ALPHA MACH
.340 100.000 .800
.675
1.007
1.265


BETA
RN
PARAMETRIC VALUES
.000 PM1
18.100
.00



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (D1E102)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	.000 PHI 18.100 .000
□	.340	100.000	.790		
◇	.675				
△	1.007				
▽	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (E1E103)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	.000 PHI 9,000
○	.340	100.000	2.000		.000
□	.675				
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (E1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA	PHI
				RN	
○	.340	107.900	.410	.000	.000
□	.675			19.100	
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (E1E101)


SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALUES
	1.377	107.900	.410	RN	.000 PHI
□	1.550				16.100
◇	1.810				
△	2.160				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (S129F) SRB FORWARD NOSE SECTION (E1E102)


SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALUES
	.340	108.000	.500	RN	.000 PHI
	.675			18.100	.000
	1.007				
	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (F1E101)


SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
	.340	107.900	.610	BETA	.000 PHI
	.675			RN	18.100
	1.007				
	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRW 033 (SA29F) SRB FORWARD NOSE SECTION (F1E101)

SYMBOL	X/D	ALPHA	MACH	PARAMETRIC VALUES	
				BETA RN	PHI .000
○	1.377	107.900	.610	18.100	.000
□	1.550				
◇	1.810				
△	2.160				




PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (F1E101)

SYMBOL
 □
 ◇
 △

X/D ALPHA MACH
 .340 107.900 .760
 .675
 1.007
 1.285


BETA PHI
 RN 18.100 .000



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (F1E101J)


SYMBOL	X/D	ALPHA	MACH	BET'	PARAMETRIC VALUES
□	1.377	107.900	.760	RN	.000 PHI
◇	1.550				18.100
△	1.810				
△	2.160				.000



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (F1E103)


SYMBOL	X/D	ALPHA	MACH	BETA	PARAMETRIC VALUES
○	.340	108.000	2.000	RN	.000 PHI
□	.675				9.000
◇	1.007				
△	1.285				



PRESSURE COEFFICIENT AROUND THE BODY AT VARIOUS STATIONS ALONG THE BODY

MSFC HRWT 033 (S429F) SRB FORWARD NOSE SECTION (RIE105)


SYMBOL	RN	X/D	ALPHA	PARAMETRIC VALUES	
○	2.250	1.810	90.000	BETA	PHI
□	10.217			MACH	180.000
					.400



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

M3FC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (R1E105)


SYMBOL	RN	X/D	ALPHA	BETA	PARAMETRIC VALUES
○	2.250	2.160	90.000	MACH	.000 PHI 180.000
□	10.217				.400



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (RIE105)


SYMBOL	RN	X/D	ALPHA	PARAMETRIC VALUES		
				BETA	PHI	
				MACH		
□	4.017	1.810	270.000		.000	180.000
◇	6.087				.400	
△	7.517					
△	9.017					



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (RIE105)


SYMBOL	RN	X/D	ALPHA	BETA	PARAMETRIC VALUES
○	13.383	1.810	270.000	MACH	.000 PHI 180.000
□	18.800				.400



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (RIE105)


SYMBOL	RN	X/D	ALPHA	PARAMETRIC VALUES	
				BETA	PHI
	4.017	2.160	270.000	MACH	180.000
□	6.067				
◇	7.517				
△	9.017				



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (R1E105)


SYMBOL	RN	X/D	ALPHA	PARAMETRIC VALUES	
○	13,383	2.160	270.000	BETA	180.000
□	18,800			MACH	.400



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E106)


SYMBOL	RN	X/D	ALPHA	PARAMETRIC VALUES		
				BETA	.000 PHI	180.000
□	2.767	1.810	270.000	KACH	.600	
△	4.050					
◇	5.650					
△	7.17					



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033.(SA29F) SRB FORWARD NOSE SECTION (B1E106)


SYMBOL	PARAMETRIC VALUES				
	RM	X/D	ALPHA	BETA	PHI
				MACH	.800
					.800
□	8.717	1.810	270.000		180.000
◇	9.687				
△	12.750				
	13.167				



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E106)


SYMBOL	RM	X/O	ALPHA	BETA	PHI
○	18.083	1.910	270.000	.000	180.000
□	20.050			.600	



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E106)


SYMBOL	RN	X/D	ALPHA	PARAMETRIC VALUES	
				BETA	PHI
□	2.767	2.160	270 °	.800	.600
◇	4.080			.800	.600
△	5.850			.800	.600
	7.417			.800	.600



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E106)


SYMBOL	RN	X/O	ALPHA	PARAMETRIC VALUES		
				BETA	.000 PHI	180.000
□	8.717	2.160	270.000	MACH	.600	
◇	9.667					
△	12.750					
	13.167					



EFFECT OF REYNOLDS NUMBER ON PRESSURE COEFFICIENTS AT VARIOUS BODY STATIONS

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (B1E106)

SYMBOL	FN	X/D	ALPHA	BETA	PARAMETRIC VALUES
□	16.083	2.160	270.000	MACH	.000 PHI 180.000
□	20.050				.600



APPENDIX
TABULATED SOURCE DATA

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRMT 033 (SA29F)

PAGE 1

MSFC HRMT 033 (SA29F) SRB FORWARD NOSE SECTION

(R1E101) (15 DEC 75)

REFERENCE DATA

SREF = 116.2600 SQ.FT. XMRP = 1044.0000 IN. XS
 LREF = 146.0000 IN. YMRP = .0000 IN. YS
 BREF = 146.0000 IN. ZMRP = .0000 IN. ZS
 SCALE = .0137

PARAMETRIC DATA

BETA = .000 PHI = .000
 RN = 18.100

MACH (1) = .410 ALPHA (1) = 72.100 Q(PSI) = 61.000 TO = 47.667 RN = 18.517 PO = 590.45

SECTION (1) SRB NOSE

DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850 1.3770 1.5500 1.8100 2.1600

THETA

.000 -.3160 -.4600 -.1690 -.4140 -.7830 -.2960 -.3180 -.3690
 22.500 -1.5360 -1.1870 -.9510 -.9010 -.6090 -.7140 -.7000
 45.000 -1.4720 -1.1590 -.8930 -.6210 -.6730 -.5370 -.7830 -.6200
 67.500 -1.9710 -1.4140 -.9320 -.6590 -.8560 -.9080 -.6310 -.5750
 90.000 -2.8050 -2.2320 -2.0130 -1.6340 -1.7280 -1.7700 -1.6450 -1.5350
 112.500 -1.8760 -1.7050 -1.5840 -1.3050 -1.3210 -1.3990 -1.4650 -1.4060
 135.000 -.5510 -.4380 -.5610 -.2830 -.2770 -.3410 -.4770 -.3430
 157.500 .6020 .4060 .3940 .6580 .6370 .2590 .5680 .5680
 180.000 .9390 .9750 1.0130 1.0270 1.0270 .9500 .9270 .9160

MACH (1) = .400 ALPHA (2) = 90.000 Q(PSI) = 61.000 TO = 47.667 RN = 18.517 PO = 590.45

SECTION (1) SRB NOSE

DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850 1.3770 1.5500 1.8100 2.1600

THETA

.000 -.6620 -.5720 -.4790 -.5210 -.4770 -.5130 -.4880 -.5540
 22.500 -.6430 -.5540 -.5540 -.6070 -.4830 -.5290 -.6030 -.5800
 45.000 -.6440 -.5390 -.6650 -.5410 -.5390 -.5660 -.5190 -.5570
 67.500 -.5620 -.5390 -.6040 -.4510 -.4560 -.5190 -.5390 -.5580
 90.000 -.8940 -1.0240 -1.1080 -1.2690 -1.3140 -1.3370 -1.3440 -1.3370
 112.500 -1.3220 -1.4090 -1.4380 -1.2590 -1.2720 -1.3500 -1.4760 -1.4370
 135.000 -.5980 -.5930 -.5920 -.4030 -.3660 -.3630 -.3980 -.3780
 157.500 .3620 .2490 .2490 .4780 .5810 .6120 .6160 .6450
 180.000 .6690 .7360 .8200 .8940 .9660 .9620 1.0090 .9870

ORIGINAL PAGE IS
 OF POOR QUALITY

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRMT 033 (SA29F)

PAGE 2

MSFC HRMT 033 (SA29F) SRB FORWARD NOSE SECTION (RIE101)

MACH (1) = .410 ALPHA (3) = 107.900 Q(PSI) = 61.000 TO = 47.667 RN = 18.517 PO = 560.45

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850 1.3770 1.5500 1.8100 2.1600

THETA

.000	-.5780	-.5480	-.4390	-.4980	-.5010	-.1070	-.4420	-.4410
22.500	-.5100	-.4480	-.4650	-.4650	-.4280	-.4280	-.5200	-.5450
45.000	-.5730	-.4530	-.6880	-.4180	-.4700	-.4310	-.4220	-.7010
67.500	-.5490	-.4950	-.4260	-.4070	-.3570	-.3930	-.4450	-.5290
90.000	-.8250	-.6550	-.2920	-.9790	-.10120	-.9020	-.11440	-.13150
112.500	-.12680	-.12490	-.13060	-.9190	-.11110	-.9650	-.9370	-.12810
135.000	-.16270	-.7500	-.16420	-.4200	-.3720	-.4140	-.3030	-.3820
157.500	.1310	.1710	.2320	.3650	.5110	.0410	.6170	.6170
180.000	.3050	.4020	.4900	.3970	.6920	.7660	.8980	.8570

MACH (2) = .600 ALPHA (1) = 72.100 Q(PSI) = 82.293 TO = 49.333 RN = 18.517 PO = 411.36

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850 1.3770 1.5500 1.8100 2.1600

THETA

.000	-1.0260	-.7520	-.5940	-.6490	-.6740	-.6010	-.4980	-.4200
22.500	-.12500	-.8830	-.7410	-.6440	-.6450	-.5180	-.5180	-.4680
45.000	-1.6290	-1.1210	-.8120	-.6180	-.6020	-.5760	-.5030	-.4870
67.500	-1.5630	-1.0160	-.7510	-.6020	-.6000	-.5660	-.5120	-.4600
90.000	-1.8580	-1.3020	-1.0620	-1.1900	-1.1790	-1.0480	-.8610	-.7370
112.500	-1.2720	-1.2370	-1.1730	-1.0040	-1.0150	-1.0850	-1.1480	-1.1920
135.000	-.1670	-.1620	-.1300	-.0270	-.0270	-.0910	-.1420	-.1520
157.500	.7270	.7270	.7550	.8130	.7960	.7640	.7420	.7070
180.000	.9890	1.0330	1.0660	1.1060	1.0890	1.0360	1.0310	.9930

MACH (2) = .600 ALPHA (2) = 90.000 Q(PSI) = 82.293 TO = 49.333 RN = 18.517 PO = 411.36

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850 1.3770 1.5500 1.8100 2.1600

THETA

.000	-.6480	-.7010	-.5810	-.6730	-.6810	-.7020	-.6290	-.5480
22.500	-.7340	-.7340	-.7280	-.7260	-.6970	-.7160	-.6080	-.5970
45.000	-.7700	-.6800	-.8030	-.6900	-.7070	-.7090	-.5910	-.5980
67.500	-.6140	-.6510	-.8370	-.5890	-.6560	-.6830	-.5930	-.5840
90.000	-.8550	-.8410	-.9600	-1.0400	-1.1090	-.9140	-.9200	-.8990
112.500	-1.3940	-1.3540	-1.3530	-1.1640	-1.1400	-1.1870	-1.2500	-1.2730
135.000	-.4000	-.3930	-.3620	-.2120	-.1470	-.1570	-.1880	-.1990
157.500	.4570	.5240	.6310	.6310	.6360	.7230	.7710	.7490
180.000	.6910	.7750	.8540	.9170	1.0140	1.0300	1.0630	1.0610

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRMT 033 (SA29F)

PAGE 3

MACH (2) = .610 ALPHA (3) = 107.900 Q(PS1) = 82.293 TO = 49.333 (RIE101) PO = 411.38

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D	.3400	.6750	1.0070	1.2850	1.3770	1.5500	1.8100	2.1600
THETA								
.000	-.7480	-.7120	-.6760	-.6760	-.6520	-.5970	-.6710	-.7080
22.500	-.7290	-.6790	-.6340	-.6340	-.6320	-.7140	-.7650	-.7650
45.000	-.7670	-.6730	-.6870	-.6710	-.6360	-.6240	-.6970	-.7420
67.500	-.6840	-.6430	-.6560	-.5700	-.5620	-.5900	-.6880	-.7070
90.000	-.7620	-.7160	-.7050	-.7850	-.9290	-.7130	-.10930	-.8760
112.500	-.13320	-.13330	-.14260	-.12410	-.11540	-.10700	-.12370	-.12380
135.000	-.6080	-.6580	-.5500	-.4410	-.3240	-.3310	-.2350	-.2530
157.500	.1350	.2170	.8680	.2840	.4380	.5670	.6330	.6310
180.000	.2990	.4060	.5120	.4780	.7320	.8310	.9310	.9220

MACH (3) = .760 ALPHA (1) = 72.100 Q(PS1) = 96.323 TO = 43.333 (RIE101) PO = 345.35

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D	.3400	.6750	1.0070	1.2850	1.3770	1.5500	1.8100	2.1600
THETA								
.000	-.8030	-.7910	-.6940	-.6800	-.6620	-.5970	-.5450	-.5130
22.500	-.7870	-.7340	-.6890	-.6890	-.6650	-.5510	-.5910	-.5470
45.000	-.7860	-.7230	-.8200	-.6490	-.6860	-.6040	-.6390	-.5210
67.500	-.7460	-.7080	-.8830	-.5640	-.7540	-.5600	-.8230	-.4800
90.000	-.8530	-.8260	-.8850	-.7260	-.9080	-.6060	-.8120	-.5340
112.500	-.8270	-.8280	-.8040	-.6880	-.6900	-.7690	-.8490	-.8870
135.000	.1220	.1170	.1110	.1770	.1840	.1310	.0940	.0730
157.500	.8180	.8680	.9110	.8930	.8660	.8420	.8130	.8130
180.000	1.0500	1.1020	1.1430	1.1610	1.1460	1.1020	1.0990	1.0620

MACH (2) = .760 ALPHA (2) = 90.000 Q(PS1) = 96.323 TO = 43.333 (RIE101) PO = 345.35

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D	.3400	.6750	1.0070	1.2850	1.3770	1.5500	1.8100	2.1600
THETA								
.000	-.6800	-.7830	-.6620	-.6620	-.7760	-.7110	-.6380	-.6400
22.500	-.7870	-.6540	-.6540	-.6690	-.7700	-.7650	-.6940	-.6700
45.000	-.8210	-.7360	-.6320	-.6160	-.7480	-.7520	-.6520	-.6480
67.500	-.7050	-.7090	-.8960	-.5340	-.6790	-.6960	-.7810	-.6460
90.000	-.8300	-.6930	-.9050	-.5290	-.6830	-.6740	-.8160	-.6440
112.500	-.10530	-.10020	-.9280	-.7990	-.8060	-.7490	-.8730	-.8770
135.000	-.1240	-.1140	-.0690	.0580	.0850	.0890	.0920	.0840
157.500	.5680	.6550	.7480	.8010	.8470	.8880	.8770	.8770
180.000	.7220	.8310	.9250	.9860	1.0740	1.1030	1.1380	1.1370

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HWIT 033 (SA28F)

PAGE 4

MACH (3) = .760 ALPHA (3) = 107.600 Q(P31) = 66.323 TO = 43.333 RW = 19.917 PO = 348.38

(R1E101)

MSFC HWIT 033 (SA28F) SRB FORWARD NOSE SECTION

SECTION (1) SRB NOSE

DEPENDENT VARIABLE CP

X/D .3400 .750 1.0070 1.2850 1.37.0 1.5500 1.8100 2.1600

THETA

.000	-.8480	-.8690	-.8050	-.7650	-.8000	-.6970	-.7310	-.7210
22.500	-.8530	-.7960	-.7960	-.7570	-.7190	-.7300	-.7210	-.7440
45.000	-.8890	-.7930	-.7450	-.7380	-.7470	-.7360	-.7020	-.7350
67.500	-.7570	-.7470	-.7000	-.6530	-.6870	-.6680	-.6990	-.7040
90.000	-.8930	-.7420	-.6910	-.6660	-.7480	-.6650	-.6620	-.7320
112.500	-1.1140	-1.1050	-1.1740	-1.0260	-1.0120	-.9260	-.9770	-.9450
135.000	-.4480	-.4440	-.3640	-.2860	-.1780	-.1470	-.0300	-.0290
157.500	.1930	.1930	.2640	.3140	.4900	.6260	.7090	.7270
180.000	.3110	.4270	.5140	.4870	.7530	.8730	.9700	.9790

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRMT 033 (SABCF)

PAGE 5

MSFC HRMT 033 (SABCF) SRB FORWARD NOSE SECTION

(RIE102) (19 DEC 75)

REFERENCE DATA

SREF = 116.2600 SQ.FT. XMRP = 1044.0000 IN. XS
 LREF = 146.0000 IN. YMRP = .0000 IN. YS
 BREF = 146.0000 IN. ZMRP = .0000 IN. ZS
 SCALE = .0137

PARAMETRIC DATA

BETA = .000 PHI = .000
 RN = 18.100

MACH (1) = .500 ALPHA (1) = 72.000 Q(PSI) = 75.080 T0 = 49.200 RN = 18.757 P0 = 506.68

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -5160 -4820 -3300 -4380
 22.500 -1.3410 -8230 -6640
 45.000 -1.7690 -1.1490 -7190 -4960
 67.500 -1.6930 -1.1470 -6570 -4320
 90.000 -2.4020 -2.0230 -1.5080 -1.3800
 112.500 -1.6110 -1.5810 -1.1240 -1.0230
 135.000 -3.3970 -3.380 -2.330 -1.0970
 157.500 .6870 .6910 .7210
 180.000 .9540 .9910 1.0540 1.0430

MACH (1) = .510 ALPHA (2) = 80.000 Q(PSI) = 75.080 T0 = 49.200 RN = 18.757 P0 = 506.68

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -8350 -5910 -5030 -5140
 22.500 -1.1250 -7530 -6030
 45.000 -1.6030 -1.0340 -6590 -4870
 67.500 -1.4440 -9330 -6270 -4350
 90.000 -1.9270 -1.5610 -1.2710 -1.2030
 112.500 -1.6990 -1.6200 -1.1560 -1.0300
 135.000 -4.4960 -4.310 -3.090 -1.1060
 157.500 .6100 .6250 .6990
 180.000 .8590 .9250 1.0030 1.0200

ORIGINAL PAGE IS
 OF POOR QUALITY

MACH (1) = .490 ALPHA (3) = 90.000 Q(PSI) = 75.080 TO = 49.200 RN = 18.757 PO = 508.88
(RIE102)

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
.000 -.5920 -.5460 -.4960 -.4550
22.500 -.5760 -.5410 -.5000
45.000 -.5810 -.5720 -.5640 -.4750
67.500 -.5970 -.5240 -.6360 -.4090
90.000 -.6230 -.7680 -.9410 -1.1690
112.500 -1.3350 -1.3670 -1.1320 -1.1040
135.000 -.5060 -.4810 -.4180 -.2440
157.500 .4810 .4850 .5780
180.000 .7040 .7900 .6690 .9110

MACH (1) = .500 ALPHA (4) = 100.000 Q(PSI) = 75.080 TO = 49.200 RN = 18.757 PO = 508.88

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
.000 -.4740 -.4590 -.4560 -.4900
22.500 -.4520 -.4140 -.4680
45.000 -.3110 -.4920 -.5210 -.4090
67.500 -.4540 -.5730 -.5120 -.3870
90.000 -.6280 -.7080 -.8520 -1.0520
112.500 -1.2080 -1.2430 -1.3130 -1.1530
135.000 -.4970 -.5350 -.4690 -.2990
157.500 .3060 .3410 .3830
180.000 .4880 .5920 .6630 .7070

MACH (1) = .500 ALPHA (5) = 108.000 Q(PSI) = 75.080 TO = 49.200 RN = 18.757 PO = 508.88

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
.000 -.4260 -.4060 -.4340 -.4110
22.500 -.3920 -.4060 -.3980
45.000 -.2720 -.4030 -.4290 -.3580
67.500 -.3880 -.3450 -.6810 -.3290
90.000 -.6520 -.5760 -.8090 -.6940
112.500 -1.1030 -1.1470 -1.4100 -1.1160
135.000 -.5530 -.5320 -.5600 -.4510
157.500 .1970 .2110 .2530
180.000 .3420 .4830 .4560 .5180

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRWT 033 (SA28F)

PAGE 7

MACH (2) = .600 ALPHA (1) = 80.000 O(PSI) = 82.715 TO = 48.000 RN = 18.757 PO = 414.82
 (RIE108)

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -.7820 -.6880 -.5610 -.4840
 22.500 -.7250 -.6130 -.5400
 45.000 -.7340 -.6840 -.6420 -.5000
 67.500 -.7300 -.6340 -.7540 -.4350
 90.000 -.7400 -.8250 -.8460 -.10920
 112.500 -1.2670 -1.2870 -.9760 -.9790
 135.000 -.2730 -.2530 -.1680 -.0410
 157.500 .6730 .6910 .7600
 180.000 .8900 .9820 1.0370 1.0640

MACH (2) = .600 ALPHA (2) = 100.000 O(PSI) = 82.715 TO = 48.000 RN = 18.757 PO = 414.82

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -.8670 -.7590 -.6650 -.6750
 22.500 -.7820 -.6580 -.7000
 45.000 -.6180 -.7600 -.7330 -.6720
 67.500 -.8090 -.7320 -.7510 -.6140
 90.000 -.9120 -.9040 -.7520 -.9510
 112.500 -1.5050 -1.4430 -1.4050 -1.1940
 135.000 -1.5600 -.5600 -.4300 -.2730
 157.500 .3140 .3690 .4290
 180.000 .4540 .6330 .6830 .7160

MACH (3) = .790 ALPHA (1) = 80.000 O(PSI) = 101.19 TO = 41.000 RN = 18.757 PO = 347.11

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -.5920 -.5930 -.6120 -.5850
 22.500 -.5900 -.6400 -.5900
 45.000 -.5820 -.5710 -.7190 -.5420
 67.500 -.5550 -.5350 -.6260 -.4950
 90.000 -.4600 -.5380 -.7600 -.5410
 112.500 -.8530 -.8510 -.6550 -.6560
 135.000 .0590 .0730 .1100 .1930
 157.500 .7970 .8200 .8860
 180.000 .9520 1.0420 1.0970 1.1400

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRWT 033 (SAL97)

PAGE 8

MSFC HRWT 033 (SAL97) SRB FORWARD NOSE SECTION (RIE102)

MACH (3) = .790 ALPHA (2) = 100.000 Q(PSI) = 101.19 TO = 41.000 RN = 18.757 PO = 347.11

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA	CP
0.000	-.8140
22.500	-.8100
45.000	-.8060
67.500	-.7890
90.000	-.7670
112.500	-.7550
135.000	-.7550
157.500	-.7550
180.000	-.7550
202.500	-.7550
225.000	-.7550
247.500	-.7550
270.000	-.7550
292.500	-.7550
315.000	-.7550
337.500	-.7550
360.000	-.7550

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRWT 033 (SA28F)

PAGE 9

MSFC HRWT 033 (SA28F) SRB FORWARD NOSE SECTION (RIE107) (15 DEC 75)

REFERENCE DATA

SREF = 116.2600 SQ.FT. XMRP = 1044.0000 IN. XS
 LREF = 146.0000 IN. YMRP = .0000 IN. YS
 BREF = 146.0000 IN. ZMRP = .0000 IN. ZS
 SCALE = .0137

PARAMETRIC DATA

BETA = .000 PHI = .000
 RN = 9.000

MACH (1) = 2.000 ALPHA (1) = 72.000 Q(PS1) = 71.840 T0 = 59.600 RN = 9.0467 PO = 200.21

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/O .3400 .6750 1.0070 1.2850

THETA

.000 -2520 -2390 -2280 -2110
 22.500 -2460 -2340 -2040
 45.000 -2580 -2380 -2270 -1740
 67.500 -2520 -2160 -2540 -1940
 90.000 -0500 -0590 -0780 -0700
 112.500 .3900 .3650 .3620 .3400
 135.000 1.0200 .9820 .9350 .9200
 157.500 1.4420 1.4490 1.4580
 180.000 1.6360 1.6410 1.6520 1.6710

MACH (1) = 2.000 ALPHA (2) = 80.000 Q(PS1) = 71.840 T0 = 59.600 RN = 9.0467 PO = 200.21

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/O .3400 .6750 1.0070 1.2850

THETA

.000 -2830 -2620 -2640 -2490
 22.500 -2760 -2670 -2490
 45.000 -2890 -2660 -2640 -2260
 67.500 -2710 -2380 -2670 -2310
 90.000 -0920 -0960 -1070 -0740
 112.500 .3180 .3020 .3080 .3360
 135.000 .9330 .9180 .9000 .9150
 157.500 1.2680 1.4190 1.4600
 180.000 1.5070 1.5710 1.6330 1.6760

ORIGINAL PAGE IS
 OF POOR QUALITY

DATE 15 FEB 76

TABULATED SOURCE DATA. MSFC HWMT 033 (SA28F)

PAGE 10

MSFC HWMT 033 (SA28F) SRB FORWARD NOSE SECTION (RIE103)

MACH (1) = 2.000 ALPHA (3) = 90.000 Q(PSI) = 71.840 TO = 59.600 RN = 9.0467 PO = 200.21

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -.2990 -.2940 -.2750 -.2670
 22.500 -.2910 -.2810 -.2620
 45.000 -.3040 -.2870 -.2770 -.2620
 67.500 -.2920 -.2750 -.2780 -.2380
 90.000 -.1470 -.1390 -.1350 -.1000
 112.500 .2200 .2060 .2390 .2830
 135.000 .7800 .8070 .7880 .8310
 157.500 1.2000 1.2610 1.3150
 180.000 1.3280 1.3970 1.4620 1.5190

MACH (1) = 2.000 ALPHA (4) = 100.000 Q(PSI) = 71.840 TO = 59.600 RN = 9.0467 PO = 200.21

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -.2840 -.2770 -.2810 -.2660
 22.500 -.2750 -.2920 -.2580
 45.000 -.3020 -.2810 -.2830 -.2140
 67.500 -.2930 -.2140 -.2890 -.2240
 90.000 -.1930 -.1740 -.1700 -.1500
 112.500 .1130 .1170 .1390 .1690
 135.000 .5770 .5970 .6170 .6740
 157.500 1.0140 1.0680 1.0790
 180.000 1.0910 1.1720 1.2280 1.2380

MACH (1) = 2.000 ALPHA (5) = 108.000 Q(PSI) = 71.840 TO = 59.600 RN = 9.0467 PO = 200.21

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D .3400 .6750 1.0070 1.2850

THETA
 .000 -.2790 -.2710 -.2600 -.2320
 22.500 -.2670 -.2890 -.2070
 45.000 -.2970 -.2770 -.2610 -.1490
 67.500 -.2910 -.1950 -.2850 -.1760
 90.000 -.2230 -.2000 -.1980 -.1940
 112.500 .0180 .0340 .0610 .0560
 135.000 .4190 .4380 .4780 .4380
 157.500 .8220 .8780 .7200
 180.000 .8690 .9520 1.0110 .8810

REFERENCE DATA

SREF = 116.2600 SO.FT.

LREF = 146.0000 IN.

BREF = 146.0000 IN.

SCALE = .0137

XMRP = 1044.0000 IN. XS

YMRP = .0000 IN. YS

ZMRP = .0000 IN. ZS

MACH (1) = .420

ALPHA (1) = 72.100

Q(PSI) = 28.210

TO = 51.000

RN = 8.4000

PO = 263.12

BETA = .000

RN = 8.400

PHI = .000

SECTION (1) SF:3 NOSE

DEPENDENT VARIABLE CP

X/D	.3400	.6750
THETA		
.000	-.3360	-.4240
22.500	-1.5200	-1.5200
45.000	-1.4640	-1.1110
67.500	-1.9910	-1.2530
90.000	-2.7080	-2.0720
112.500	-1.7980	-1.6390
135.000	-.5050	-.4200
157.500	.6080	.6080
180.000	.9530	.9790

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRWT 033 (SA29F)

PAGE 12

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (RIE105) (15 DEC 75)

REFERENCE DATA

SREF = 116.2600 SQ.FT. XMRP = 1044.0000 IN. XS
LREF = 146.0000 IN. YMRP = .0000 IN. YS
BREF = 146.0000 IN. ZMRP = .0000 IN. ZS
SCALE = .0137

RN (1) = 2.250 ALPHA (1) = 90.000 Q(PS1) = 7.2900 TO = 37.000 RN = 2.2900 PO = 67.800

SECTION (1) SRB NOSE

X/D 1.8100 2.1600

THEIA

.000 -.2970 -.3280
22.500 -.3460 -.5040
45.000 -.2950 -.6170
57.500 -.3600 -.3810
90.000 -1.1850 -.6800
112.500 -.9110 -1.1110
135.000 -.1930 -.3280
157.500 .7770 .7130
180.000 1.0940 1.0100

RN (2) = 4.017 ALPHA (1) = 270.000 Q(PS1) = 13.370 TO = 51.000 RN = 4.0167 PO = 128.12

SECTION (1) SRB NOSE

X/D 1.8100 2.1600

THEIA

.000 -.8240 -.3290
22.500 -.3780 -.4360
45.000 -.3440 -.5200
57.500 -.3130 -.4080
90.000 -.9300 -.7900
112.500 -1.0820 -1.0290
135.000 -.1950 -.3290
157.500 .7780 .7330
180.000 1.0400 .9360

PARAMETRIC DATA

BETA = .000 PHI = 180.000
MACH = .400

DEPENDENT VARIABLE CP

DEPENDENT VARIABLE CP

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRNT 033 (SA28F)

PAGE 13

RN (3) = 6.067 ALPHA (1) = 270.000 Q(PS1) = 19.930 TO = 46.000 RN = 6.0667 PO = 191.41
 (R1E106)

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA
 .000 -.4970 -.3640
 22.500 -.4230 -.4710
 45.000 -.3860 -.4620
 67.500 -.3500 -.4470
 90.000 -.1.0390 -.9970
 112.500 -.1.1240 -.1.1270
 135.000 -.1.1930 -.3040
 157.500 -.7940 -.7260
 180.000 1.0570 .9570

RN (4) = 7.517 ALPHA (1) = 270.000 Q(PS1) = 25.360 TO = 49.000 RN = 7.5167 PO = 238.79

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA
 .000 -.6830 -.3810
 22.500 -.3710 -.4440
 45.000 -.3770 -.5360
 67.500 -.3590 -.4490
 90.000 -.1.1760 -.1.0560
 112.500 -.1.0970 -.1.1430
 135.000 -.1.1880 -.2910
 157.500 .7840 .7290
 180.000 1.0930 .9920

RN (5) = 9.017 ALPHA (1) = 270.000 Q(PS1) = 30.220 TO = 49.000 RN = 9.0167 PO = 266.83

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA
 .000 -.4970 -.3990
 22.500 -.4270 -.4900
 45.000 -.4190 -.4810
 67.500 -.3890 -.4190
 90.000 -.1.1960 -.1.0620
 112.500 -.1.1630 -.1.1630
 135.000 -.2150 -.3070
 157.500 .7860 .7240
 180.000 1.0400 .9510

ORIGINAL PAGE 18
 OF POOR QUALITY

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRWT 033 (SA29F)

PAGE 14

MSFC HRWT 033 (SA29F) SRB FORWARD NOSE SECTION (RIE105)

RN (6) = 10.217 ALPHA (1) = 90.000 Q(PSI) = 32.730 TO = 38.000 RN = 10.217 PO = 315.66

SECTION (1) SRB NOSE

X/D 1.8100 2.1600

THETA
.000 -.5620 -.4110
22.500 -.4120 -.5210
45.000 -.4410 -.6560
67.500 -.4160 -.4710
90.000 -1.2170 -1.0880
112.500 -.8640 -1.2060
135.000 -.2320 -.3320
157.500 .7580 .7240
180.000 1.0640 .9870

RN (7) = 13.383 ALPHA (1) = 270.000 Q(PSI) = 44.620 TO = 48.000 RN = 13.383 PO = 424.20

SECTION (1) SRB NOSE

X/D 1.8100 2.1600

THETA
.000 -.4980 -.3880
22.500 -.4220 -.4910
45.000 -.4210 -.4700
67.500 -.4000 -.4750
90.000 -1.2630 -1.1380
112.500 -1.2110 -1.1970
135.000 -.2370 -.3190
157.500 .7380 .7060
180.000 1.0250 .9430

RN (8) = 18.800 ALPHA (1) = 270.000 Q(PSI) = 61.330 TO = 44.000 RN = 18.800 PO = 580.08

SECTION (1) SRB NOSE

X/D 1.8100 2.1600

THETA
.000 -.5780 -.4420
22.500 -.5150 -.5190
45.000 -.4410 -.4950
67.500 -.4810 -.5000
90.000 -1.3490 -1.3620
112.500 -1.3240 -1.3260
135.000 -.2740 -.3500
157.500 .1340 .6350
180.000 1.0550 .9790

DATE 19 FEB 76

TABULATED SOURCE DATA, MSFC HRMT 033 (SA29F)

PAGE 15

MSFC HRMT 033 (SA29F) SRB FORWARD NOSE SECTION

(RIE106) (15 DEC 75)

REFERENCE DATA

SREF = 116.2600 SO.FT. XMRP = 1044.0000 IN. XS
LREF = 146.0000 IN. YMRP = .0000 IN. YS
BREF = 146.0000 IN. ZMRP = .0000 IN. ZS
SCALE = .0137

PARAMETRIC DATA

BETA = .000 PHI = 180.000
MACH = .600

RN (1) = 2.767 ALPHA (1) = 270.000 Q(PS1) = 12.990 TO = 49.000 RN = 2.7667 PO = 64.300

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA
22.500 -.5150 -.4450
45.000 -.4590 -.4710
67.500 -.4560 -.5630
90.000 -.4450 -.5820
112.500 -.5480 -1.2770
135.000 -1.1640 -1.2470
157.500 -.1140 -.1760
180.000 1.1350 1.0650

RN (2) = 4.050 ALPHA (1) = 270.000 Q(PS1) = 19.680 TO = 41.000 RN = 4.0500 PO = 92.220

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA
22.500 -.3080 -.3500
45.000 -.4140 -.3930
67.500 -.4100 -.4300
90.000 -.4090 -.3970
112.500 -.6300 -.4270
135.000 -1.1160 -1.1090
157.500 -.1130 -.1580
180.000 1.1100 1.0570

MSFC HRMT 033 (SAP9F) SRB FORWARD NOSE SECTION (RIE108)

RN (3) = 5.850 ALPHA (1) = 270.000 Q(PS1) = 27.260 TO = 46.000 RN = 5.8500 PO = 136.57

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA

.000 - .6340 - .4350
 22.500 - .5110 - .4700
 45.000 - .4950 - .4970
 67.500 - .4740 - .4930
 90.000 - .7760 - .6240
 112.500 - 1.1700 - 1.1540
 135.000 - 1.180 - 1.1770
 157.500 .8110 .7890
 180.000 1.1360 1.0600

RN (4) = 7.417 ALPHA (1) = 270.000 Q(PS1) = 34.410 TO = 51.000 RN = 7.4167 PO = 175.40

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA

.000 - .6520 - .5930
 22.500 - .6470 - .6690
 45.000 - .6190 - .6430
 67.500 - .6260 - .6350
 90.000 - .9320 - .7470
 112.500 - 1.2460 - 1.2930
 135.000 - .1580 - .2140
 157.500 .8030 .7730
 180.000 1.0950 1.0590

RN (5) = 8.717 ALPHA (1) = 270.000 Q(PS1) = 40.290 TO = 47.000 RN = 9.7167 PO = 204.15

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA

.000 - .6690 - .5390
 22.500 - .6580 - .6700
 45.000 - .6340 - .6590
 67.500 - .6360 - .6480
 90.000 - .9210 - .7670
 112.500 - 1.2350 - 1.2500
 135.000 - .1550 - .2090
 157.500 .8050 .7740
 180.000 1.1030 1.0530

DATE 19 FEB 76

TABULATED SOURCE DATA. MSFC HRMT 033 (SA2SF)

PAGE 17

MSFC HRMT 033 (SA2SF) SRB FORWARD NOSE SECTION (RIE108)

RN (6) = 9.667 ALPHA (1) = 270.000 Q(PSI) = 44.820 TO = 51.000 RN = 9.667 PO = 229.65

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA	CP
0.000	-7040 -6390
22.500	-6890 -7170
45.000	-6620 -7040
67.500	-6640 -7000
90.000	-9620 -8190
112.500	-12470 -12900
135.000	-1590 -2110
157.500	8050 7820
180.000	10910 10630

RN (7) = 12.750 ALPHA (1) = 270.000 Q(PSI) = 58.920 TO = 47.000 RN = 12.750 PO = 298.82

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA	CP
0.000	-7240 -6230
22.500	-6870 -7040
45.000	-6630 -7110
67.500	-6660 -6720
90.000	-9650 -8210
112.500	-12340 -12300
135.000	-1620 -2080
157.500	7910 7320
180.000	11240 10590

RN (8) = 13.167 ALPHA (1) = 270.000 Q(PSI) = 60.110 TO = 41.000 RN = 13.167 PO = 303.58

SECTION (1) SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA	CP
0.000	-7420 -6370
22.500	-6800 -6820
45.000	-6590 -7650
67.500	-6610 -6730
90.000	-9800 -8130
112.500	-12280 -12230
135.000	-1480 -1950
157.500	7910 -22760
180.000	11090 10580

MSFC HRNT 033 (SA29F) SRB FORWARD NOSE SECTION (RIE108)

RN (9) = 18.083 ALPHA (1) = 270.000 Q(PST) = 74.630 TO = 49.000 RN = 18.083 PO = 378.90

SECTION (1)SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA	
.000	-.7470
22.500	-.5880
45.000	-.7260
67.500	-.8190
90.000	-.7090
112.500	-.7260
135.000	-1.0410
157.500	-1.2540
180.000	-1.2550
	-1.1710
	-2.2120
	-3.1300
	-7840
	-3.1300
	1.1140
	1.0600

RN (10) = 20.050 ALPHA (1) = 270.000 Q(PST) = 90.350 TO = 36.000 RN = 20.050 PO = 451.37

SECTION (1)SRB NOSE DEPENDENT VARIABLE CP

X/D 1.8100 2.1600

THETA	
.000	-.6480
22.500	-.6040
45.000	-.6410
67.500	-.6540
90.000	-.5330
112.500	-.7100
135.000	-.5330
157.500	-.6310
180.000	-.9440
	-.8180
	-1.2230
	-1.2280
	-1.1510
	-1.1910
	-3.7420
	-7970
	-3.7420
	1.0970
	1.0860